SpeedBOX CELLOFANATRICE UNIVERSALE

UNIVERSAL OVERWRAPPING MACHINE - ENCELOFANAR UNIVERSALES

SpeedBOX is a professional, universal machine made for cellophane wrapping / packaging of any type of box or other type of packaging with cellophane, folds and welds typical of perfumes and cigarette packs. It is special designed for cosmetics, medical items, candles soaps, games, food, sweets, candles, soaps, gadgets, CD / DVD / BluRay or other items of your imagination. **SpeedBOX** adapts to all the needs of small to medium runs, saving a very expensive and difficult industrial process. You can produce at home or restore the packaging of any box quickly with results identical to the very expensive industrial machines. Thanks to the use of the same reels for professional use, you can cut the film, make precise creases and seals, perfectly wrapping your box without any waste or scrap.

There are 2 versions the **SpeedBOX-35** and **SpeedBOX -50 wide** differentiated according to the maximum width of the bobine that they can manage. They are completely manual machines, but acquiring a discreet operation you can pack up to 150 boxes per hour which vary according to the size of the box.

Make your own packaging at home, greatly reducing costs and enormous logistics problems!

CHANGE FORMAT SIMPLY PREPLACING THE REE



SUITABLE FOR ANY NEEDS WITH OPTIONAL MODULES



SEALING POINT MODULE: (Available Standard and PRO-DIG) Give your packs more elegance by fixing the sides flaps of the cellophane in one place as in high-level cosmetics. **CUTTING MODULE:** Ideal for the needs of packaging always different boxes, it allows to trim excess cellophane adapting it to your needs good for sampling or to restore boxes. **STRIP DISPENSER:** You can insert the quick opening tape typical of the candy packages to easily unwrap the package.







THECNICAL DATA:

Packaging: any type of rigid / semi-rigid box Production capacity: up to 150 pieces per hour (variable according to size) Film cutting: Automatic thermal blade ni / cr Welding: Stabilized thermal panel Default panel operating temperature: 135 ° Heater temperature stability: ± 1 Temperature: room setting -150 ° step 1 ° Internal thermal protection Adjustable Cellophan tension-clutch Thermal blade engagement protection Cellophan: COEX Bi-Oriented Polypropylene (BOPP) Usable cellophane thickness: 25/30/35 Mic Maximum reel width: SpeedBOX: 35 cm - SpeedBOXwide: 50 cm Maximum reel diameter: 28cm (11 ") Dimensions: SpeedBOX35 42x19x45 / SpeedBOX50 56x19x45 (reel exc.) Power supply: 110VAC / 60Hz - 220VAC / 50Hz - 350W Weight: net 10Kg / 17kg - reel excluded - 100% CE PARTS ONLY ADD ON - OPTIONS : 1-SEALING POINT MODULE - Analogic Fixed temp incl. mounting braket 2-SEALING POINT PROFESSIONAL - Digital controlled Variable 3-CONTINUOUS CUTTING MODULE - Allow to Trim the mounted film

4-STRIP DISPENSER MODULE - Strip for quick package opening **5-EXTRA SPOOL BAR -** Additional bar set for a quick reel replacement

PRODUCTION & DISTRIBUTION:

www.europalink.net - info@europalink.net Via Oddo Stocco 6 – 30030 SALZANO–VE- IT Tel. +39.041484737 - Fax.+39.041.8620282 YOUTUBE : www.youtube.com/europalinknet



PERFECT FOR COSMETICS